



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Killer Cans
Product Use Description : Solvent-borne coatings, Primers
Company : Alsa Corporation
2640 East 37th Street
Vernon, CA 90058
Telephone : 1-323-581-5200
Fax : 1-323-589-4400
Emergency telephone number : (800) 535-5053 / (352)323-3500

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Regulatory status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Signal Word : DANGER
Form : aerosol
Odour : characteristic
Odour - Control parameters : no data available
Hazard Summary : Flammable.

Irritant
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C / 122 °F. Flammable Aerosol May cause fire.

Potential Health Effects

Eyes : May cause eye irritation.
Skin : May cause skin irritation.
Target Organs : Skin
Eyes
Central nervous system

Carcinogenicity:

NTP : No component of this product which is present at levels greater than or equal to 0.1 % is identified as a known or anticipated carcinogen by NTP.

IARC : No component of this product which is present at levels greater than or equal to 0.1 % is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA : No component of this product which is present at levels greater than or equal to 0.1 % is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
acetone; propan-2-one; propanone	67-64-1	>= 45 - < 50
propane	74-98-6	>= 25 - < 35
butane	106-97-8	>= 20 - < 25
2-methoxy-1-methylethyl acetate	108-65-6	>= 2 - < 3

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area. Never give anything by mouth to an unconscious person. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). When symptoms persist or in all cases of doubt seek medical advice. Take off all contaminated clothing immediately.
- Inhalation : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
- Skin contact : Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners.
- Eye contact : Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
- Ingestion : If a person vomits when lying on his back, place him in the recovery position. Clean mouth with water and drink afterwards plenty of water. Ingest activated charcoal. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5. FIRE-FIGHTING MEASURES

- Form : aerosol
Flash point : < 0 °C (< 32 °F)
Ignition temperature : 365 °C (689 °F)
Lower explosion limit : 1.4 %(V)

- Upper explosion limit : 8.5 %(V)
- Suitable extinguishing : Use water spray, alcohol-resistant foam, dry chemical or media carbon dioxide.
- Extinguishing media which : High volume water jet must not be used for safety reasons Specific hazards during fire : Fire will produce dense black smoke containing hazardous fighting combustion products (see heading 10). Do not use a solid water stream as it may scatter and spread fire.
- Special protective : Use personal protective equipment. equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Use water spray to cool unopened containers. Exposure to decomposition products may be a hazard to health. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Ventilate the area.
Remove all sources of ignition
Avoid inhalation of vapor or mist.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Should not be released into the environment.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.
- CERCLA Hazardous substances and corresponding RQs :

67-64-1	5,000 lbs <i>final RQ</i>
74-98-6	100 lbs <i>final RQ</i>
106-97-8	100 lbs <i>final RQ</i>

SECTION 7. HANDLING AND STORAGE

Handling

- Handling : Do not breathe vapors or spray mist. Avoid contact with skin and eyes. Take precautionary measures against static discharges. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Limit the stocks at work place. Do not spray on a naked flame or any other incandescent material. Use only in well-ventilated areas. For personal protection see section 8.
- Advice on protection against fire and explosion : Keep away from heat and sources of ignition. Do not smoke. Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Electrical equipment should be protected to the appropriate standard.



Wash contaminated clothing before re-use.
Handle in accordance with good industrial hygiene and safety practice.
General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:	aerosol
Odor	:	characteristic
Flash point	:	< 0 °C (< 32 °F)
Ignition temperature	:	365 °C (689 °F)
Thermal decomposition	:	Heating can release hazardous gases., Fire or intense heat
Lower explosion limit	:	1.4 %(V)
Upper explosion limit	:	8.5 %(V)
Vapor pressure	:	3.6 %(V) at 20 °C (68 °F)
Density	:	0.85 g/cm ³ at ca.20 °C (68 °F)
Volatile organic compounds	:	51.86 %

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid	:	Heat, flames and sparks.
Materials to avoid	:	Strong acids and strong bases Oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), dense black smoke.
Thermal decomposition	:	Heating can release hazardous gases. Fire or intense heat may cause violent rupture of packages.
Hazardous reactions	:	Vapors may form explosive mixture with air. Note: No decomposition if used as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Skin irritation	:	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin.
Eye irritation	:	The liquid splashed in the eyes may cause irritation and reversible damage. Strong lachrymation can make it difficult to escape.
Carcinogenicity	:	No data is available on the product itself.
Toxicity to reproduction	:	No data is available on the product itself.
Teratogenicity	:	No data is available on the product itself.
Further information	:	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Liver and kidney injuries may occur. Even the smallest quantities that enter into the lung due to swallowing or subsequent vomiting can lead to a pulmonary edema or pneumonia.

Component:

Acetone; propan-2-one; 67-64-1
propanone

Acute oral toxicity: LD50 rat
Dose: 5,800 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: 20,000 mg/kg

Acute inhalation toxicity: LD50 rat
Dose: 70 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to eyes.
Result: Moderate eye irritation

Propane 74-98-6

Skin irritation: Classification: Irritating to skin.
Result: Skin irritation

Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

2-methoxy-1-methylethyl 108-65-6
acetate

Acute oral toxicity: LD50 mouse
Dose: 8,532 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: 7,500 mg/kg

Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

SECTION 12. ECOLOGICAL INFORMATION

Adsorbed organic bound : not included
Halogen (AOX)
Volatile organic compounds : 51.86 %
(VOC) content
Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Adequate disposal : In accordance with local and national regulations. Please ensure aerosol cans are sprayed completely empty (including propellant) Containers that have not been emptied in compliance with regulations are regarded as hazardous waste.

SECTION 14. TRANSPORT INFORMATION

DOT 49 CFR

Proper shipping name	: AEROSOLS
UN-No.	: 1950
Class	: 2.1
Packing group	:
Emergency Response	: 126
Guidebook Number	

TDGR

Proper shipping name	: AEROSOLS
UN-No.	: 1950
Class	: 2.1
Packing group	:
Emergency Response	: 126
Guidebook Number	

ICAO / IATA-DGR

UN UN-No.	: 1950
Description of the goods	: AEROSOLS
Class	: 2.1
ICAO-Labels	: 2.1
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203
Packing instruction (passenger aircraft)	: Y203

IMDG-Code

UN-No.	: UN 1950
Description of the goods	: AEROSOLS
Class	: 2.1
IMDG-Labels	: 2.1
EmS Number	: F-D S-U
Marine pollution	: no

SECTION 15. REGULATORY INFORMATION

OSHA Hazards	: Flammable Aerosol Moderate skin irritant Moderate eye irritant
TSCA Status	: On TSCA Inventory
DSL Status	: All components of this product are on the Canadian DSL list.
SARA 311/312 Hazards	: Fire Hazard Acute Health Hazard

PENN RTK

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

<u>Components</u>	<u>CAS-No.</u>
Acetone; propan-2-one; propanone	67-64-1
Propane	74-98-6
Butane	106-97-8

MASS RTK

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Acetone; propan-2-one; propanone	67-64-1
Propane	74-98-6
Butane	106-97-8

NJ RTK

US New Jersey Worker and Community Right-to-Know Law (New Jersey Statute Annotated Section 34:5A-5)

Acetone; propan-2-one; propanone	67-64-1
Propane	74-98-6
Butane	106-97-8
2-methoxy-1-methylethyl acetate	108-65-6

California Prop. 65

: This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

SECTION 16. OTHER INFORMATION

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.